


COPPER CONNECTORS



10103 T45° Copper cable lug 45°

T45° cable lug manufactured from electrolytic copper tubing with a tin-plated surface finish to electrical contact. Its particular orientation makes it suitable for installations where connection needs a specific placement.

According to IEC 61238-1-1 standard.

Code	Ref.	Section (mm ²)		Dimensions (mm)						Kg x 100	Bag	Box
				ØI	L	ØT	A	C1	C2			
007270	T45-10/6	10	6	4.7	10	6.4	11.9	7.0	6.0	0.391	100	800
007280	T45-10/8		8			8.3	15.0	8.0	8.0	0.400	100	800
007320	T45-16/6	16	6	5.6	11	6.4	11.9	7.0	6.0	0.518	100	600
007330	T45-16/8		8			8.3	15.0	8.0	7.5	0.527	100	600
007370	T45-25/8	25	8	7.1	13	8.3	15.0	8.5	7.5	0.731	50	350
007380	T45-25/10		10			10.5	18.0	11.0	10.0	0.803	50	350
007420	T45-35/8	35	8	8.7	16	8.3	15.7	9.0	8.0	1.157	50	250
007430	T45-35/10		10			10.5	19.0	11.0	10.0	1.219	50	200
007520	T45-50/10	50	10	9.8	19	10.5	20.0	11.0	10.0	1.822	20	120
007530	T45-50/12		12			13.0	21.0	13.0	12.0	1.768	20	120
007580	T45-70/10	70	10	11.5	21	10.5	21.5	11.0	10.0	2.470	20	100
007590	T45-70/12		12			13.0		12.0	11.0	2.514	20	100
007660	T45-95/14	95	14	13.5	24	14.5	24.7	15.0	13.0	3.606	20	60
007670	T45-95/16		16			16.5	27.0	16.0	15.0	3.619	20	60
007720	T45-120/14	120	14	15.6	28	14.5	28.9	16.0	14.0	5.948	10	50
007730	T45-120/16		16			16.5		17.0	16.0	6.260	10	40
007770	T45-150/14	150	14	16.5	32	14.5	30.4	18.0	16.0	7.814	10	40
007780	T45-150/16		16			16.5			16.0	7.618	10	30
007830	T45-185/16	185	16	18.8	34	16.5	34.0	18.0	17.0	10.540	10	20
007880	T45-240/16	240	16	21.2	38	16.5	38.4	18.0	17.0	13.126	5	20