


COPPER CONNECTORS



10105 TT NF C20-130 Tulip copper cable lug

TT cable lug manufactured from electrolytic copper tubing with a tin-plated surface finish to improve electrical contact.
The tulip shape at the end of the barrel facilitates the introduction of the cable.

According to NF C20-130 standard.

Code	Ref.	Section (mm ²)		Dimensions (mm)							x 100	Bag	Box
				ØE	ØI	L	ØT	A	C1	L2			
009220	TT-6/5	6	5	5.5	3.3	30.50	5.3	13.0	8.0	11.0	0.243	100	1200
009230	TT-6/6		6			32.50	6.5				0.366	100	1000
009270	TT-10/6	10	6	6.8	4.3	30.50	6.5	12.0	6.5	12.0	0.598	100	800
009280	TT-10/8		8			37.00	8.5				0.485	100	600
009320	TT-16/6	16	6	8.0	5.3	33.30	6.5	12.0	6.3	14.0	0.712	100	500
009330	TT-16/8		8			37.50	8.5				0.752	100	500
009360	TT-25/6	25	6	9.5	6.6	36.30	6.5	13.0	6.3	15.0	0.874	50	300
009370	TT-25/8		8			42.00	8.5				1.022	50	300
009380	TT-25/10		10			46.00	10.5				1.139	50	250
009420	TT-35/8	35	8	11.0	7.9	44.00	8.5	17.0	10.0	17.0	1.591	50	200
009430	TT-35/10		10			49.00	10.5				1.592	50	200
009510	TT-50/8	50	8	12.5	9.2	47.00	8.5	18.0	12.0	19.0	2.109	20	140
009520	TT-50/10		10			52.00	10.5				2.264	20	140
009530	TT-50/12		12			54.00	13.0				2.101	20	120
009570	TT-70/8	70	8	15.0	11.0	51.00	8.5	21.0	10.0	21.0	2.241	20	100
009580	TT-70/10		10			55.00	10.5				3.357	20	80
009590	TT-70/12		12			59.00	13.0				3.449	20	80
009640	TT-95/10	95	10	17.0	13.1	60.00	10.5	25.0	12.0	22.0	4.518	20	60
009650	TT-95/12		12			62.00	13.0				4.292	20	60
009660	TT-95/14		14			66.50	15.0				4.354	20	60
009670	TT-95/16		16			70.00	17.0				4.714	20	60
009710	TT-120/12	120	12	19.0	14.5	66.00	13.0	28.0	13.0	26.0	6.544	10	50
009720	TT-120/14		14			69.50	15.0				5.972	10	50
009730	TT-120/16		16			72.00	17.0				6.198	10	50
009760	TT-150/12	150	12	21.0	16.2	73.00	13.0	30.0	15.0	30.0	8.578	10	40
009770	TT-150/14		14			73.00	15.0				8.069	10	40
009780	TT-150/16		16			75.00	17.0				7.865	10	40
009810	TT-185/12	185	12	23.0	18.0	81.00	13.0	33.5	16.0	32.0	10.255	10	40
009830	TT-185/16		16			87.00	17.0				10.596	10	30
009860	TT-240/12	240	12	26.0	20.6	93.50	13.0	38.0	21.5	35.0	14.383	5	25
009880	TT-240/16		16			93.50	17.0				14.240	5	25
009920	TT-300/16	300	16	28.0	23.0	102.00	17.0	41.0	19.0	44.0	16.270	5	10
009950	TT-400/16	400	16	32.0	26.0	115.00	17.0	46.5	19.0	44.0	26.819	4	8