



COPPER CONNECTORS



10109 CP Pin terminal

CP pin terminal manufactured from electrolytic copper tubing with a tin-plated surface finish to improve electrical contact. Its design makes it suitable for those applications of the conductor to the clamp.

Code	Ref.	Section (mm ²)	Dimensions (mm)					Kg x 100	Bag	Box
			ØE	ØI	L	A	L1			
025100	CP-1.5	1.5	3.5	1.7	17.0	2.0	10.0	0.600	100	2000
025110	CP-2.5	2.5	4.2	2.5	17.5	2.0	10.0	0.700	100	2000
025120	CP-6	6	6.0	3.7	20.0	2.5	10.0	1.490	100	1500
025130	CP-10	10	6.8	4.7	25.0	5.0	12.0	0.423	100	1000
025140	CP-16	16	7.8	5.6	31.0	6.0	15.0	0.573	100	800
025150	CP-25	25	9.4	7.1	34.0	7.0	18.0	0.829	100	500
025160	CP-35	35	11.3	8.7	42.0	9.0	18.0	1.420	100	300
025170	CP-50	50	12.6	9.8	46.0	10.0	21.0	1.849	50	200



10109 CPP Connection tip isolated

CPP connectors are made from electrolytic copper tubing with a tin-plated surface finish for improved electrical contact. The design facilitates connection of the cable lugs in the terminals.

The shape of the cable end facilitates cable insertion.

The insulation provides an additional degree of protection.



Code	Ref.	Section (mm ²)	Dimensions (mm)							Kg x 100	Bag	Box
			ØE	ØI	L	L1	G	A	T			
025180	CPP-10	10	9.0	4.5	29.5	15.5	2.4	4.3	1.1	0.290	100	600
025190	CPP-16	16	10.5	5.9	35.0	19.0	2.6	5.5	1.2	0.470	100	300
025200	CPP-25	25	11.5	7.0	44.5	24.5	2.6	6.8	1.2	0.750	100	200
025210	CPP-35	35	14.0	8.7	54.0	29.5	3.2	8.0	1.5	1.320	50	150
025220	CPP-50	50	15.8	9.8	61.0	35.0	3.8	9.5	1.8	2.040	50	100
025230	CPP-70	70	18.0	11.6	75.0	44.0	4.2	11.0	2.0	3.310	25	50
025240	CPP-95	95	21.6	13.5	75.0	44.0	5.2	12.5	2.5	4.740	20	40